

DYNASCAN

UV-202

REF: UV202
EAN: 8435550819598

DUAL-BAND WALKIE-TALKIE HAM RADIO

Robust and reliable, the **Dynascan UV-202** redefines the amateur radio experience. This analog device combines flawless **VHF/UHF** transmission with **airband reception**. A solid, modern, and complete solution for those seeking **advanced functionality** and reliability in any situation

HIGHLIGHTS

- **Dual-band VHF/UHF transmission:**
TX: 144–146 MHz / 430–440 MHz
RX: 108–174 MHz / 400–479.995 MHz
- **FM reception** (76–108 MHz) and **Airband AM reception** (108–136 MHz)
- **Maximum power:** 5W
- **Color TFT display:** clear visualization of channels, frequencies, and settings
- **200 alphanumeric memories**, perfect for quick and professional organization
- **USB-C for charging**
- **Extensive operating functions:**
 - CTCSS, DCS, DTMF, tone-burst
 - Internal VOX
 - Noise cancellation
 - Half-duplex mode (V/V – U/U)
 - Multiple scan modes

**VHF/UHF with
Airband
Reception**



Ensures complete protection against dust and sand, and protection against the effects of temporary immersion.

DYNASCAN

UV-202 DUAL-BAND WALKIE-TALKIE HAM RADIO



TECHNICAL SPECIFICATIONS

- Channeling:
25 kHz (wideband), 12.5 kHz (narrowband)
- Protection rating: IP67
- Antenna Impedance: 50Ω
- Modulation Type:
11K0F3E (12,5kHz) / 16K0F3E (25kHz)
- Operating Temperature: -20°C a +55°C
- Power Supply: 7.4 V/2600 mAh Lithium-Ion Battery
- Duty cycle: 5-5-90 (TX-RX-Standby)
- Dimensions: 121 x 58 x 42 mm (without antenna)
- Weight: 330 g (with antenna and battery)

CONTENT

- Dynascan UV-202 Transceiver
- Antenna
- 7.4V/2600mAh Li-Ion Battery
- Desktop Charger
- AC/DC Power Adapter
- Belt Clip
- User Manual in Spanish, English, French and Portuguese

